




















TPE Power cable | CF300.UL.D






- for maximum load requirements
- TPE outer jacket
- oil-resistant, biooil-resistant
- flame-retardant
- UV-resistant
- hydrolysis-resistant and microbe-resistant

	Conductor	Conductor cable consisting of pre-leads (following EN 60228).
	Core insulation	Mechanically high-quality TPE mixture.
	Outer jacket	Low-adhesion mixture on the basis of TPE, especially abrasion-resistant and highly flexible, adapted to suit the requirements in energy chains®. Colour: Jet black (similar to RAL 9005)
	Bending radius	moved minimum 7,5 x d fixed minimum 4 x d
	Temperature	moved -35 °C to +90 °C fixed -40 °C to +90 °C
	v max. unsupported/gliding	10 m/s, 6 m/s
	a max.	100 m/s ²
	Travel distance	Freely suspended travel distances and up to 400 m for gliding applications, Class 5
	Torsion	± 90 °, with 1 m cable length
	UV-resistant	High
	Nominal voltage	600/1000 V (following DIN VDE 0250).
	Testing voltage	4000 V (following DIN VDE 0281-2).
	Oil	Oil-resistant (following DIN EN 60811-2-1), biooil-resistant (following VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4.
	Flame-retardant	According to IEC 60332-1-2, CEI 20-35, FT1, VW-1
	Silicon-free	Free from silicon which can affect paint adhesion (following PV 3.10.7 – status 1992).
	UL/CSA	Style 10492 and 21218, 1000 V, 80 °C
	NFPA	Following NFPA 79-2012 chapter 12.9
	CEI	Following CEI 20-35
	CE	Following 2006/95/EG

 eplan download, configurator ► www.igus.eu/CF300

1030 types from stock no cutting costs ...
(for up to 10 cuts of the same type)

Class 6.5.4 (6 maximum load requirements 5 travel distance up to 400 m 4 oil-resistant)

	DESINA	According to VDW, DESINA standardisation
	Lead free	Following 2011/65/EC (RoHS-II)
	Clean room	According to ISO Class 1. Outer jacket material complies with CF34.UL.25.04.D, tested by IPA according to standard 14644-1
	CTP	Certified according to N° C-DE.PB49.V.00397
	EAC	Certified according to N° TC RU C-DE.ME77.B.00964

New! Guaranteed lifetime for this series according to the "chainflex® guarantee club" conditions ► Page 22-25

Double strokes*		5 million			7,5 million		10 million
Temperature, from/to [°C]	v max. [m/s]	a max. [m/s ²]	Travel distance [m]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-35 / -25				10	11	12	
-25 / +80	10	6	100	≤ 400	7,5	8,5	9,5
+80 / +90					10	11	12


* higher number of double strokes possible

Typical application area

- for maximum load requirements
- almost unlimited resistance to oil, also with bio-oils
- Indoor and outdoor applications, UV-resistant
- freely suspended travel distances and up to 400 m for gliding applications
- Storage and retrieval units for high-bay warehouses, machining units/machine tools, quick handling, clean room, semiconductor insertion, ship to shore, outdoor cranes, low-temperature applications

Delivery program Part No.	Number of cores and conductor nominal cross section [mm ²]	External diameter max. [mm]	Copper index [kg/km]	Weight [kg/km]
CF300.UL.40.01.D	1x4,0	6,5	38	61
CF300.UL.60.01.D	1x6,0	7,0	62	83
CF300.UL.100.01.D	1x10,0	8,0	106	128
CF300.UL.160.01.D	1x16,0	9,5	167	197
CF300.UL.250.01.D	1x25,0	11,5	264	300
CF300.UL.350.01.D	1x35,0	12,5	370	411
CF300.UL.500.01.D	1x50,0	14,5	528	570
CF300.UL.700.01.D	1x70,0	16,5	766	810
CF300.UL.950.01.D	1x95,0	19,0	1009	1088
CF300.UL.1200.01.D	1x120,0	21,5	1276	1357
CF300.UL.1500.01.D	1x150,0	23,0	1529	1552
CF300.UL.1850.01.D	1x185,0	27,0	2079	2167

Note: The mentioned external diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core

 **Order example: CF300.UL.950.01.D – in your desired length (0,5 m steps)**
CF300.UL.D chainflex® series .950 Code nominal cross section .01 Number of cores

 **prices** price list online
www.chainflex.eu/CF300

 **delivery time** despatched in 24 hours or today

... no minimum order quantity ...

igus® GmbH Cologne | Tel. +49(0)2203/9649-800 Fax -222 | info@igus.de | www.chainflex.eu

